

INNOVATION MAKES MASTERPIECE.

# D16A

**HOT / COLD**

Super High Capacity POU Cooler  
Designed and Built Specifically for  
High Volume Use  
Great for Large Offices or Families  
Height = 44.9"



## Point of Use Water Cooler D16A Specifications

MODEL	D16A
COLD WATER	1.3 GAL/HR OF 50 F
HOT WATER	1.84 GAL/HR OF 185 F
ROOM TEMP.WATER	N/A
DIMENSIONS	11.4" W x 14.4" D x 44.9" H
SHIPPING WEIGHT	55 lbs

※ Specifications are subject to change without notice.

- COLD AND HOT WATER  
THE ABOVE RATES TESTED IN AMBIENT TEMP 90°F WATER INLET TEMPERATURE 80°F

### CABINET

Top and front panels are molded of ABS plastic and side panels are made of electric zinc coated steel with high polymer polyester resin.

### FAUCETS

Durable polypropylene. Self closing type. Easy to operate. Safety hot water faucet.

### DRIP TRAY

Concealed, lift-out design, high impact, durable ABS plastic. Removable, anti-splash grid diverts drip water.

### REFRIGERATION UNIT

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector.  
No lubricant is needed. Refrigerant is controlled by accurately calibrated capillary tube.

### HOT WATER THERMOSTAT

Water Temperature is controlled to 185°F by an automatic thermostat.  
ON/OFF switch is easily accessible on the rear control panel.

### HOT WATER TANK

Hygienic stainless steel tank with a highly efficient internal heating element..

### COLD WATER THERMOSTAT

Easily control the temperature from 39.2°F - 50°F by using the adjustable, easily located thermostat on the back panel

### COLD WATER TANK

High capacity, hygienic stainless steel tank. Large enough volume for most RO filtration systems.

### LG BRAND COMPRESSOR

All Clover coolers come standard with a LG brand compressor.  
Each cooler has LG's highest quality compressor with the low cycle rates.

